



POLYGRIP

CONSTRUCTION ADHESIVE, FOR
BONDING STRUCTURAL BUILDING
MATERIALS

DATA SHEET UPDATED 30/07/2024

Product information

Paintable sealant, extra white, professional use.

- + Strong suction cup effect
- + Strong initial tack
- + Strong adhesion
- + Solvent free
- + Low elasticity modulus
- + No shrinkage
- + Low VOC

Recommended uses

- Structural bonding construction adhesive
- All types of metal sheets, flashings and gutters
- Vertical applications
- Polystyrene and polyurethane panels and elements, indoors and outdoors
- Adhesion for non-absorbent elements (metal, glass, plastic), indoors and outdoors

Coverage

About 18/20 m (linear) per cartridge

Application instructions

Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be covered with our extra-light filler SUPRIMO LIGHT FILLER.

Product preparation

Mono-component adhesive and ready-to-use. Cut the seal of the cartridge and use a special caulking gun for cartridges.

Application

Apply the product all over the contact surface.

Cleaning

Clean the equipment with a nitro diluent.

Technical product data

Base	Silane Modified polymers
Appearance and colour	Extra White
Solids percentage	about 80%
Customs code	39095090



POLYGRIP

CONSTRUCTION ADHESIVE, FOR
BONDING STRUCTURAL BUILDING
MATERIALS

DATA SHEET UPDATED 30/07/2024

Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 30-40 min
Setting Time	48-72 hours
Size	300 ml

Warning

Do not use at temperatures below +3 °C
Application is recommended between +10 °C and +35 °C

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

The information described in this Technical Data Sheet is based on our decades-long experience but is indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assume responsibility for its use.