



ELASTIC PAINTABLE SEALANT

ACRYLIC-ELASTIC SEALANT

DATA SHEET UPDATED 29/07/2024

Product information

Paintable, acrylic based sealant, extra white, professional use.

- + Strong suction cup effect
- + Strong initial tack
- + Up to 400% stretch
- + Solvent free
- + Low shrinkage
- + No nails support required
- + Elastic
- + Paintable

Recommended uses

- Sealing cracks on walls, plasterboards and tiles
- Sealing joints between plasterboard and metal supports
- Polystyrene and polyurethane panels, frames and rosettes
- Cork and thermo-acoustic materials
- DIY applications

Coverage

About 18/20 m (linear) per cartridge

Application instructions

Surface preparation

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler SUPRIMO LIGHT FILLER.

Product preparation

Mono-component adhesive and ready-to-use. Cut the seal of the cartridge and use a special caulking gun for cartridges.

Application

Apply the product all over the contact surface.

Cleaning

Clean the equipment with fresh water immediately after use, or remove mechanically.

Technical product data

Base	Acrylic
Appearance and colour	Extra White
Solids percentage	about 85%

ELASTIC PAINTABLE SEALANT

ACRYLIC-ELASTIC SEALANT



DATA SHEET UPDATED 29/07/2024

Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 20 min
Setting Time	24/36 hours
Size	300 ml

Warning

Do not use at temperatures below +3 °C
Application is recommended between +10 °C and +35 °C

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.