



## LIGHT FILLER

---

### SUPER LIGHTWEIGHT FILLER

DATA SHEET UPDATED 25/07/2024

---

#### Product information

Super lightweight filler with significant thermal insulating properties. Particularly suitable for humid environments.

- + Solvent free
- + No cracks
- + No shrinkage
- + No need for sanding
- + Ready-to-use
- + Extra White
- + High yield

---

#### Recommended uses

- Filling holes, cracks, fissures, and missing parts on walls, wood, and ceramics, with a thickness ranging from 1 mm to over 5 cm
- Restoring specific areas affected by rising dampness; provides thermal insulation
- Paintable with any type of paint or water-based varnish
- Ideal for plastering polystyrene and polyurethane frames and rosettes
- Effective for filling plasterboard joints
- Designed for indoor use

---

#### Coverage

Determined by the thickness of the filling.

---

#### Application instructions

##### Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils.

##### Product preparation

Mono-component acrylic-based filler, ready-to-use.

##### Application

Apply the product with a semi-flexible spatula or blade for fillers.

##### Cleaning

Clean equipment with fresh water immediately after use, or remove mechanically.



## LIGHT FILLER

### SUPER LIGHTWEIGHT FILLER

DATA SHEET UPDATED 25/07/2024

Technical product data	Base	Acrylic
Appearance and colour		Dense paste, extra white
Solids percentage		About 80%
Customs code		3506 9100
Application temperature		+10°C +35°C
Waiting Time		None
Open Time		About 30–40 minutes
Setting Time		48–72 hours

#### Warning

Do not use at temperatures below +3 °C.  
Application is recommended between +10 °C and +35 °C.

#### Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

#### Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.