



DATA SHEET UPDATED 25/07/2024

Product information

Universal powder adhesive for wallpaper.

- + Stainless
- + High grab
- + High yield
- + Zero VOC (Volatile Organic Compounds)
- + Ready to use in 5 minutes from dilution

Recommended uses

- Wallpapers
- Vinyl wallcoverings with paper-backing
- Expanded vinyl wallcoverings with paper-backing up to 250 g/m²
- Duplex wallpaper

Dilution table for 200 gr	WALLCOVERING	DILUTION	m ²
	Fixing	10 L	-
	Wallpaper	6 L	40 - 45
	Lightweight vinyl	5 L	35 - 40

Application instructions

Surface preparation

All surfaces must be clean, dry, absorbent, and free from dust, paint, and oil. Any cracks or holes in the wall must be filled with our light SUPRIMO LIGHT FILLER and smoothed with a normal plaster filler in case of imperfections. We recommend using primer for preparation and cleaning, and our SUPRIMO (created for resistance to mildew and bacteria) where the walls are damp.

Product preparation

The product should be diluted in clean water in the proportions as shown in the dilution table.

1. Stir the water vigorously
2. Tip the contents of the pack of powder into the water, continuing to stir.
3. Leave to settle for 3 minutes
4. Continue to stir
5. After a further 5 minutes the product is ready to be used

Application

WA

WALLPAPER ADHESIVE



DATA SHEET UPDATED 25/07/2024

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

Cleaning

It is recommended to wipe off any excess paste from joints and edges using a damp cloth. THIS PRODUCT DOES NOT LEAVE ANY MARKS.

Technical product data

Description of Product	Powder
Colour	white
Percentage of Solids	100%
Customs Classification	3505 2030
Flame Resistance	no
Application Temperature	+5°C +40°C
Fixing Time	10-20 minutes
Open Time	20-30 minutes
Complete Drying Time	48 hours
Not Harmful	
Frost Resistant	

Warning

Do not use this product on a non-absorbent surface, do not apply to damp or mouldy walls, or where the surface has not been prepared adequately. Any excess paste on the surface must be wiped off immediately using a damp cloth.

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 60 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.