

## EASY READY-MIX

CLEAR WALLPAPER ADHESIVE



DATA SHEET UPDATED 23/07/2024

### Product information

Natural resin-based paste ready-to-use adhesive for all types of wallpapers, including fiberglass and commercial weight wallcoverings.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)



### Recommended uses

- Heavy vinyl wallpapers with paper or non-woven backing
- Heavyweight, paintable and non-paintable non-woven wall coverings
- Expanded wall coverings
- Fiberglass wall coverings, any thickness
- Thermal and sound absorbing wall coverings

### Coverage

Approximately 150-250 g/m<sup>2</sup>, depending on the porosity of the substrate.

### Application instructions

#### Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be filled with our extra-light stucco SUPRIMO LIGHT FILLER. We always recommend using our Primer SUPRIMO PRIMER SP to fix and prevent mouldings on the walls.

#### Product preparation

SUPRIMO EASY READY-MIX is a ready-to-use product however, when necessary, dilute it with clean water up to a maximum of 5/10%.

#### Application

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

#### Cleaning

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano)

+39 02 90361148

[www.suprimo.it](http://www.suprimo.it)

## EASY READY-MIX

CLEAR WALLPAPER ADHESIVE



DATA SHEET UPDATED 23/07/2024

### Technical product data

Base	Natural Resin
Appearance and colour	White cream
PH	6.5
Viscosity	40000-50000 cps
VOC	< 2 µg/ m <sup>3</sup>
Solids percentage	> 35%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	20-30 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

### Warning

SUPRIMO EASY READY-MIX is not suitable for non-absorbent substrates, damp walls with mold, or surfaces that are not properly prepared. Any adhesive spills should be immediately cleaned up with a damp sponge. Keep out of reach of children and pets. Dispose of waste in designated containers for building materials.

### Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.